

Sales Specification

OXLUBE L9-TMP





General data

CAS-No. Version 126-57-8

Date of issue 15.05.2020

Product No. 51006133 51006143 51006183

Additional product number(s) may be in use for other packaging

Sales Specification

Property		Limit	Unit	Test Method
Appearance		Clear and bright		Visual examination
Water	max.	0.03	% (w/w)	ASTM E1064 / ASTM E203
Acid number	max.	0.05	mg KOH/g	DIN EN ISO 2114 / ASTM D974
Platinum/Cobalt Color (Hazen/APHA Color)	max.	100		DIN EN 1557 / DIN EN ISO 6271 / ASTM D5386

Typical values

Specific Gravity at 15 °C	0.93 – 0.95		DIN EN 51757 / ASTM D4052
Density at 20°C 2)	0.94	g/cm³	DIN EN 51757 / ASTM D4052
Kinematic Viscosity at 100 °C 1)	4.4 – 4.7	mm²/s	ASTM D445
at 40 °C 1)	19.5 – 22.5	mm²/s	ASTM D445
Viscosity Index 2)	138		ASTM D2270
Pour Point 1)	max 39	°C	ASTM D5950 / ASTM D5985
Flash Point 1)	min. 250	°C	DIN 51736 / ASTM D92
Ester content 1)	min. 98.5	% (w/w)	Gas Chromatography
Total metal content 2) (sum of Ag, Cd, Cu, Fe, Ni, Pb, Sn)	max. 10	mg/kg	ASTM D5185

Remarks

- Product conforms to limit but test is not routinely performed and value is not listed on the Product Quality Report (PQR)
- Parameter is not specified; typical value based on non-routinely performed measurements will be reported on the Product Quality Report (PQR)

The parameters given in the Sales Specification table are listed on the Product Quality Report (PQR) Non-standard Test methods used are available upon request (due to Copy Right). Contact your Sales Support for copies.

Page 1 of 1 11660 OQ SLS EN V1.docx

Typical properties not especially listed are given in the appropriate SDS, they are not part of the sales specification.

This information is based on our present state of knowledge and shall be intended to provide general notes on our products and their field of application. It shall therefore not be construed as guaranteeing specific characteristics of the products described and/or their suitability for a particular application. Any existing industrial property rights shall be observed. The quality of our products is warranted under our General Conditions of Sale.